

VRC Raptor[™] Cold Spray System

Deployable 21kW
Heater and Powder
Feeder



Fully Enclosed Ruggedized Construction


- System Pressure up to 1000 PSI (69 Bars)
- Heater temp up to 1472°F (800°C)
- Max Gas Flow 88 CFM (2500 SLM)
- 10ft (3M) Thermally Insulated Hoses
- Single or Dual Gas Train - Nitrogen or Helium
- Data & Capture Download

Transporting Features

- Foldable Tow Hitch
- Fork Pockets
- Lifting Eyes
- Tie Downs



www.vrcmetalsystems.com



Hand-Held or Robotic Applications

Nozzle Applicator only 4.4lbs (2kg)



VRC[®]

METAL SYSTEMS


Tethered Parameter Readout With
Touch Screen Controls



Foldable Tow Hitch

Stowable Heater and
Powder Feeder

Lifting Eyes




Front View

Dimensions
68"L x 32"W x 65"H
(173cmL x 82cmW
x 165cmH)

Overall Weight
900lbs (408 kg)

Electrical
480 VAC, 3 PH, 50 AMP



www.vrcmetalsystems.com

sales@vrcmetalsystems.com

600 N Ellsworth Road Box Elder, South Dakota 57719

Sales: 605-716-0065

© 2021 VRC Metal Systems, LLC, All Rights Reserved. THIS DOCUMENT CONTAINS PROPRIETARY AND CONFIDENTIAL INFORMATION AND IS THE SOLE PROPERTY OF VRC METAL SYSTEMS, LLC. ANY FORM OF REPRODUCTION, DISSEMINATION, COPYING, DISCLOSURE, MODIFICATION, DISTRIBUTION AND OR PUBLICATION OF THIS MATERIAL, IN PART OR IN WHOLE, TO A THIRD PARTY, WITHOUT PRIOR WRITTEN CONSENT OF VRC METAL SYSTEMS, LLC, IS STRICTLY PROHIBITED

MKS0006 REV B